

REMARKS

This Preliminary Amendment cancels original claims 1 to 10 in the underlying PCT Application No. PCT/EP2004/002594 and adds new claims 11 to 20. The new claims conform the claims to the U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.125, the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including the Title and Abstract) are to conform the Specification and Abstract to U.S. Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. § 1.121 and § 1.125, a Marked Up Version Of The Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. In the Marked Up Version, underlining indicates added text and "strike-throughs" and double-brackets indicate deleted text. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

Also enclosed is a translated copy of the International Search Report dated August 18, 2004. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is asserted that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,
KENYON & KENYON

Dated: 9/13/2005

By:

Gerard A. Messina
Gerard A. Messina
Reg. No. 35,952

One Broadway
New York, New York 10004
Telephone: (212) 425-7200

CUSTOMER NO. 26646

(Signature)
Reg. No.
33,865
Avaron C
DEPT 104

STEERING DEVICE FOR VEHICLES HAVING A PAIR OF WHEELS
WHICH CAN BE STEERED FREELY BY MEANS OF LATERAL FORCES

Description

5 FIELD OF THE INVENTION

The present invention relates to a steering device for a vehicle according to the preamble of patent claim 1.

RELATED APPLICATION INFORMATION

10 This application is based on International patent application no. PCT/EP2004/002954, and therefore claims priority to German patent application no. 103 10 942, which was filed on March 13, 2003 in the German patent office. The contents of both applications in their entirety is hereby incorporated by reference.

15 BACKGROUND INFORMATION

The exemplary embodiments and/or exemplary methods of the present invention relate to a steering device for a vehicle.

Such a steering device is known from DE 198 03 745 A1. for a vehicle is discussed in German patent document no. 198 03 745.

20 The vehicle describeddiscussed there has a freely steerable axle which is also referred to as a self steering axle and whose steering can be locked as a function of predefined operating states of the vehicle. In particular, the intention is that this steering system will be locked

25 when a minimum velocity of the vehicle is exceeded.

Furthermore, sensors for sensing the velocity of the vehicle, the steering angle of the steerable axle and brake pressure are provided and are connected to an electronic control device. Depending on predefined measured values of

the sensors, the electronic control device releases a locking device for the self steering axle or activates it.

DEGerman patent document no. 100 65 186 A1

~~describes~~discusses a hydraulically activated steering device
5 of a utility vehicle with two axles which can be steered actively by ~~means of~~ a hydraulic system. An electronically controllable damping valve is connected into the hydraulic circuit and can be adjusted to a stored characteristic curve as a function of the load state of the vehicle.

10 DEGerman patent document no. 198 12 238 A1

~~describes~~discusses a method for controlling the yaw behavior of vehicles. Sensors for the vehicle velocity and the steering angles are connected to a control unit which determines the yaw rate of the vehicle. Two independent
15 control circuits for a steering intervention and a braking intervention control the yaw rate in accordance with a predefined setpoint value.

Heavy trucks and many buses have a third axle in addition to a front axle which can be steered by the driver and a
20 driven, nonsteerable rear axle. If the third axle is arranged behind the driven axle, it is referred to as a "trailing axle".

A distinction is made between vehicles in which the third axle is rigid, i.e. cannot be steered, and the vehicles in
25 which it is steerable. In the case of steerable third axles, a distinction is further made between axles which are coupled kinematically to the front axle steering system, i.e. which are also steered automatically by the driver together with the front axle and what are referred to as
30 "lateral force steered axles". Lateral force steered axles are not coupled to the steering system of the vehicle and

are therefore also referred to as "freely steerable axles".
If the vehicle travels round a bend, laterally directed
positive forces arise between the underlying surface and the
wheels of the lateral force steered axle and lead to an
5 "automatic" steering lock.

In comparison to other multi-axle vehicles in which a
plurality of axles are arranged rigidly, i.e. one behind the
other in a nonsteerable fashion, the wear on the tires in
vehicles with steerable "additional axles" is less, in
10 particular when cornering at low velocities, and the vehicle
has a better turning circle. However it is considered to be
disadvantageous that vehicles with one or more freely
steerable axles have a smaller degree of "lateral rigidity"
and thus worse stability on bends compared to vehicles with
15 nonsteerable axles.

In particular in the case of low coefficients of friction
and on a smooth underlying surface, vehicles with freely
steerable axles tend to oversteer more readily than vehicles
with rigid axles. The tendency to oversteer is increased
20 further if the nonsteered axle is driven and also has to
transmit drive forces in addition to the lateral guiding
forces.

~~From the applicant internal prior art~~ As understood, vehicles
with a second rear axle are known which are steered by
25 lateral force and in which the lateral force steered axle
can be locked "where necessary", i.e. in which the degree of
freedom of the steering can be locked. The locking or
blocking is carried out here exclusively as a function of
the velocity of the vehicle, with the axle being locked
30 above a specific minimum velocity. Such vehicles have
significantly improved lateral rigidity at relatively high
velocities compared to vehicles with a lateral force steered

axle which cannot be locked. At the same time, the free steerability at low velocities allows the wear on tires to be reduced.

5 SUMMARY OF THE INVENTION

The An object of the exemplary embodiments and/or exemplary methods of the present invention is to provide a steering device for further improving the driving stability of vehicles with a lateral force steered axle, in particular in
10 order to reduce the risk of oversteering.

This object ~~is~~ may be achieved by ~~means of the features of patent claim 1.~~ the systems and methods described herein. Advantageous refinements and developments ~~of the invention can be found in the subclaims~~ are also described herein.

15 ~~The basic principle of the~~ An aspect or feature of the exemplary embodiments and/or exemplary methods of the present invention is to control the locking or blocking of a lateral force steered axle on the basis of a plurality of criteria, specifically as a function of the velocity of the
20 vehicle, and additionally as a function of variables which characterize the instantaneous driving stability or lane holding of the vehicle.

The driving state of a vehicle can be described approximately by ~~means of a~~ complicated vector variable
25 which is composed, for example, of the components of wheel speeds, wheel acceleration values, slip values at individual wheels, translatory and rotational vehicle acceleration or yaw rate, mass of the vehicle, distribution of axle load, steering angle, engine torque, braking torque at individual
30 wheels etc.

By monitoring a plurality of such variables and by ~~means of~~
a comparison with predefined "critical" individual values or
critical combinations of individual values ~~it is possible to~~
~~estimate~~, the instantaneous driving stability of the vehicle
5 may be estimated more realistically. If a critical driving
situation is detected, the driving stability, in particular
the lateral stability when cornering, can be improved by
locking the lateral force steered axle.

In order to monitor the driving state ~~it is possible to use~~,
10 an electronic stability system which is usually present in
any case in modern vehicles may be used. In addition to the
locking of the lateral force steer axle, interventions can
also be made into the engine torque, and braking
interventions can be made at an individual wheel or at a
15 plurality of wheels.

According to one development of the exemplary embodiments
and/or exemplary methods of the present invention, a locking
device which is provided for locking the lateral force
steered axle is activated by ~~means of~~ a central electronic
20 control device. If the driving state of the vehicle has
stabilized again as a result of the control intervention,
the lateral force steered axle can be "released" again.

According to one development of the exemplary embodiments
and/or exemplary methods of the present invention, an axle
25 is not released again until predefined values which
characterize a critical driving situation are undershot for
a specific minimum period of time of, for example, 3-5 sec,
i.e. if the vehicle has stabilized for a significantly long
time.

30 The locking device may be capable of being activated
hydraulically or pneumatically, for example.

According to one development of the exemplary embodiments
and/or exemplary methods of the present invention, steering
levers which are connected to one another in an articulated
fashion by ~~means of~~ a track rod are provided on the wheels
5 which are at opposite ends of the lateral force steered
axle. One of the two steering levers may have, for example,
an "extension" which serves as a locking lever and engages
in a locking mechanism.

~~The invention will be explained in more detail below by
10 means of an exemplary embodiment and in conjunction with the
drawing, in which:~~

BRIEF DESCRIPTION OF THE DRAWINGS

~~fig.~~Figure 1 ~~is~~shows a basic outline of a three-axle vehicle
with a lateral force steered axle when cornering, ~~and fig.~~

15 Figure 2 is a more detailed illustration of the vehicle
according to ~~fig.~~Figure 1.

DETAILED DESCRIPTION

Fig. 1 shows a vehicle 1, for example a bus, with a front
axle which can be steered by the driver by ~~means of the~~
20 steering wheel and which is formed by two wheels 2 and 3.
The vehicle 1 also has a driven rear axle which is rigid,
i.e. cannot be steered, and has rear wheels 4 and 5.

"Behind" the rear axle a lateral force steered trailing axle
is provided which is formed by the wheels 6 and 7 which are
25 coupled to one another by ~~means of a~~ steering mechanism 8.

When cornering, the driver predefines a steering lock by
~~means of the~~ front wheels 2 and 3. When the vehicle is
traveling in a stable way, the wheels 6 and 7 which are
coupled by ~~means of~~ the steering mechanism 8 move freely. As
30 a result of the lateral positive forces which occur between

the underlying surface and the wheels 6 and 7, a corresponding steering lock is brought about automatically at the lateral force steered axle. In the case of the steering lock of the wheels 2, 3 and 6, 7 shown in fig. 1
5 all the wheels 2-7 have a common, imaginary instantaneous pole M which permits stable cornering.

Fig. 2 is an enlarged illustration of the vehicle in fig. 1. Each of the wheels 2-7 is assigned a wheel sensor 9-14 for determining the wheel speeds V_2-V_7 and for determining the
10 steering angles $\alpha_2, \alpha_3, \alpha_6, \alpha_7$ of the wheels 2, 3, 6, 7. The signals which are supplied by the sensors 9-14 are evaluated by an electronic control device 15. Purely by way of example, two further sensors are illustrated, specifically a yaw rate sensor 16 and a coupling force sensor 17 which
15 determines the coupling force on the king pin. Alternatively or in addition ~~it is possible to provide~~ further sensors may be provided for monitoring the instantaneous driving stability, for example brake pressure sensors for determining the brake pressures at individual wheels, load
20 sensors for determining the axle load distribution and the mass of the vehicle, longitudinal acceleration sensors and/or lateral acceleration sensors etc.

The two wheels 6 and 7 of the lateral force steered axle each have a steering lever 18 or 19 which is permanently
25 connected to the wheel suspension. The two steering levers 18, 19 are connected to one another in an articulated fashion by ~~means of a~~ track rod 20. The two wheels 6, 7 thus have a common "degree of steering freedom". The steering lever 19 of the wheel 7 has an "extension" which serves as a
30 locking lever 21. When the wheels 6, 7 make steering movement, the locking lever 21 swivels with them. The locking device 22 which is illustrated only schematically

here can lock the locking lever 21. Therefore, both wheels 6 and 7 are "locked" by the locking device 22.

The locking device 22 can be actuated electronically by the control device 15, specifically as a function of the
5 velocity of the vehicle and a plurality of measured variables which characterize the driving stability and are sensed by sensors 9-14, 16, 17 which are illustrated only schematically here.

To summarize, the exemplary embodiments and/or exemplary
10 methods of the present invention can be characterized as follows:

~~The basic idea of the~~An aspect of the exemplary embodiments
and/or exemplary methods of the present invention is that,
in a vehicle with one or more lateral force steered rear
15 axles, the rear axle steering systems are locked not only as a function of velocity but also in the case of oversteering or in other critical driving situations. This may be done by "retrofitting" an electronic stability system which is provided in any case in the vehicle and which actuates the
20 locking device for the lateral force steered rear axle, i.e. locks when necessary and registers it again after critical situations.

This steering device is suitable, for example, for a bus with three axles in which the central rear axle is driven
25 and the last axle is steered by lateral force and is locked from approximately 40 km/h by ~~means of~~ pneumatic cylinders or hydraulic cylinders. The bus is equipped, for example, with a conventional electronic stability system which is capable of detecting oversteering. If the oversteering of
30 the bus exceeds a specific threshold value, the locking mechanism is activated by the electronic control device by

~~means of~~ a digital output using a pneumatic or hydraulic valve, and the lateral force steered rear axle is locked, as a result of which an additional lateral guiding force builds up at the steered rear axle and stabilizes the vehicle.

- 5 After the vehicle has been traveling straight ahead again in a stable fashion for a certain time, i.e. for a period of time of 3-5 sec, the locking mechanism is released again and the rear axle steering system is released again.

Of course, a plurality of such lockable, lateral force
10 steered axles may also be provided in one vehicle.

ABSTRACT OF THE DISCLOSURE

A steering device for vehicles having a pair of wheels which can be steered freely as a function of the current driving state of the vehicle or whose steered position can be locked
5 by an electronically actuatable locking device, having an electronic control device and having sensors which are connected to the electronic control device and have the purpose of monitoring current driving state values, with the electronic control device actuating the locking device when
10 a minimum velocity of the vehicle is exceeded, in such a way that the steered position of the pair of wheels is locked, characterized in that driving state values which characterize critical driving situations are additionally stored in the electronic control device, in which the
15 steered position of the pair of wheels is locked in critical driving situations, and in which, after a critical driving situation, the locking device does not release the pair of wheels again until predefined critical driving state values are undershot at least for a predefined period of time.